

LUMIPLUS PAR56 LAMP

To correctly light a swimming pool we recommend you: Install a lamp in the range LumiPlus 1.11 every 20 m² of water surface. Install a lamp in the range LumiPlus 2.0 every 20 m² of water surface. **Note:** Recommendation valid for light coloured pools. In darker coloured pools or stainless steel pools we recommend oversizing the proportion of projectors per m².



PAR56 1.11	White	RGB	RGB DMX
Lamp	52596 AT AT	56001 ENRIGHT	56002 NRG()
Consumption	16 W (24 VA)	27 W (37 VA)	27 W (37 VA)
Luminous Flux	1.485 lm	1.100 lm	1.100 lm

Rated Voltage: 12 V AC Protection: IPX8
Cable not included.

It always has to be installed submerged in water. Made to order, is possible to supply the PAR56 LEDs LAMP in this emission of colours: Red / Green / Blue / Warm White / Neutral White.



PAR56 RGB 1.11 wireless lamp	1 lamp + Control Motion 59126	2 lamps + Control Motion	1 lamp RGB 1.11 Wireless 59124 🙈	
Consumption	27 W (37 VA) each lamp			
Luminous Flux	1.100 lm each lamp			

Rated Voltage: 12 V AC Protection: IPX8 Cable not included. It always has to be installed submerged in water. Motion Control LumiPlus not waterproof.



PAR56 2.0	White	RGB	RGB DMX	
lamp	43412 ENERGY LINE CONTINUES AND	43411 ENERGE IN CHIPPONT - SYCHOLOGY	45637 ENERGY, III	
Consumption	58 W (60 VA)	48 W (64 VA)	48 W (64 VA)	
Luminous Flux	4.320 lm	2.544 lm	2.544 lm	

Rated Voltage: 12 V AC Protection: IPX8 Cable not included. It always has to be installed submerged in water. Made to order, is possible to supply the PAR56 LEDs LAMP in this emission of colours: Red / Green / Blue / Warm White / Neutral White.



PAR38 lamp	37661
Light colour	White
Consumption	34 W (47 VA)
Luminous Flux	800 lm

Rated Voltage: 12 V AC Protection: IPX8 E27 Socket. It always has to be installed submerged in water.Made to order, is possible to supply the PAR38 LEDs lamp in this emission of colours: Red / Green / Blue / Warm White / Neutral White.





LUMIPLUS PAR56 PROJECTORS

To correctly light a swimming pool we recommend you: Install a lamp in the range LumiPlus 1.11 every 20 m² of water surface. Install a lamp in the range LumiPlus 2.0 every 20 m² of water surface. **Note:** Recommendation valid for light coloured pools. In darker coloured pools or stainless steel pools we recommend oversizing the proportion of projectors per m².







PAR56 1.11 Projector						
			Face	Plate	Consump-	Luminous
Light co	lour	Fixation	ABS	Stainless Steel	tion	Flux
DCD	for proposed from the second s	STD	56003	56004	27 W	1.100 lm
KGB	RGB	Global	53838 😂	-	(37 VA)	
VAVI- 14 -	Service of the latest and latest	STD	52599	52600	16 W	
White	the summaries week out and benefits do time another or an	Global	53839 🗟	-	(24 VA)	1.485 lm
RGB	Star properties have been seen and start of the seen and start of the seen and start of the seen and s	STD	56005	56006	27 W	
DMX	Minimizer acceptance year for the second control of the second con	Global	53842 😂	-	(37 VA)	1.100 lm

Rated Voltage:12 V AC Protection: IPX8

Cable: 2,5m. H07RN-F 2x1,5 mm² It always has to be installed submerged in water. The Global projectors are seawater resistants only concrete pool. Projectors without niche: to complete the projector select the right niche for each swimming pool, see page 9.



PAR56 RGB 1.11 wireless	1 projector + 1 Control Motion	2 projectors + 1 Control Motion	1 projector RGB 1.11 Wireless
projector Indicate the project of th	59128 🗟	59129 😂	59130 😂
Consumption	27 W (37 VA) each projector		
Luminous Flux	1.100 lm each projector		

Rated Voltage:12 V AC Protection: IPX8 Cable: 2,5m. H07RN-F 2x1,5 mm2 It always has to be installed submerged in water. Motion Control LumiPlus not waterproof. Projector with Global fixation system. ABS Face Plate.



PAR56 2.0 projector						
			Face	Face Plate		Luminous
Light co	lour	Fixation	ABS	Stainless Steel	Con- sumption	Flux
DCD	In a security base in the control of	STD	45619	45620	48 W	2.544 lm
KGD	RGB	Global	53841 🗟	-	(64 VA)	
\\/\b:+c	Interpretation from the control of t	STD	45621	45622	58 W	4.320 lm
White	Side Sentineting remolecus and benefit devides remolecus this senting-out-wife on always analysis.	Global	53840 😂	-	(60 VA)	
RGB	RGB DMX	STD	45640	45641	48 W	
DMX		Global	53843 😂	-	(64 VA)	2.544 lm

Rated Voltage:12 V AC Protection: IPX8
Cable: 2,5 m. H07RN-F 2x1,5 mm²
It always has to be installed submerged in water.
The Global projectors are seawater resistants only concrete pool.
Projectors without niche: to complete the projector select the right niche for each swimming pool, see page 9.







LUMIPLUS S-LIM PROJECTORS

To correctly light a swimming pool we recommend you: Install a lamp in the range LumiPlus 1.11 every 20 m² of water surface. Install a lamp in the range LumiPlus 2.0 every 20 m2 of water surface. Note: Recommendation valid for light coloured pools. In darker coloured pools or stainless steel pools we recommend oversizing the proportion of projectors per m².



S-LIM 1.11 Projector							
		Swimming	Face	Face Plate		Luminous	
Light	colour	pool	ABS	Stainless Steel	Con- sumption	Flux	
DCD	Interpretation for the state of	Concrete	56022 😂	56023	27 W	1.100 lm	
RGB	Prefabricated	56024 😂	56025	(37 VA)	1.100 IIII		
VA/I= :+ =	Interpretation from the state of the state o	Concrete	56030 😂	56031	16 W	1 405 1	
White	La Lilemann de print prosperiore La Lilemann de print prosperiore Data enigene la larga ser nos espiracións. AUV200-2	Prefabricated	56032 😂	56033	(24 VA)	1.485 lm	
RGB DMX	Concrete	56026 😂	56027	27 W	1 100		
	Prefabricated	56028 😂	(37 VA)		1.100 lm		

Rated Voltage:12 V AC Protection: IPX8 Cable: 2,5m. H07RN-F 2x1,5 mm² It always has to be installed submerged in water.



S-LIM 2.11 Projector						
		Swimming	Face	Face Plate		Luminous
Light o	colour	pool ABS Stainless Steel			Consump- tion	Flux
DOD	the property from the property of the property	Concrete	56010 😂	56011	48W	2.544 lm
RGB	Les Simpores de més proportion (de la Simpores de més proportion (de la Simpores de més proportion (de la Simpores de més proportion de la Simpores de més de la Simpores d	Prefabricated	56012 😂	56013	(64 VA)	2.544 IIII
White	http://www.initiation.com/	Concrete	56018 😂	56019	58 W	4.320 lm
White	Les limpares de réde prospertur De projectur limps aux nos présidents	Prefabricated	56020 😂	56021	(60 VA)	
RGB	Bits proved for low gray months and gray month	Concrete	56014 😂	56015	48W	2.544.1
DMX	Prefabricated	56016	56017	(64 VA)	2.544 lm	

Rated Voltage:12 V AC Protection: IPX8 Cable: 2,5m. H07RN-F 2x1,5 mm² It always has to be installed submerged in water.



S-LIM RO wireless projecto	}	1 projector + 1 Control Motion	2 projectors + 1 Control Motion	1 projector RGB 1.11 Wireless
Swim- Concrete ming		61314	61315	61318
Pool	Prefabricated	Prefabricated 61316 61317		61320
Consumption		27 W (37 VA) each projector		
Luminous	uminous Flux 1.100 lm each projector			tor

Rated Voltage:12 V AC Protection: IPX8 Cable: 2,5m. H07RN-F 2x1,5 mm² It always has to be installed submerged in water. ABS Face Plate. Control LumiPlus not waterproof.
















Niches for Lumiplus DESIGN				
Concrete	Prefabricated	Swimming Pool	KIT for fixing	
Swimming Pool	With injerts	Self-tapping screws	other niches	
59813 🗟	59818 *			

^{*} Compatible with most 180 to 190 mm Ø niches on the market (Hugo Lahme, MTS Produckts, Wibre, etc.). Ask your dealer for further details.



Niches for LumiPlus Mini					
Concrete Swimming Pool		Prefabricated	Panelled Swim-	Liner Swimming	
Light gut	Quick coupling	Swimming Pool	ming Pool	Pool	
06967	53956 😂	00369	49828	60229*	

* Compatible with Mini 3.13





ACCESORIES

RGB CONTROL SYSTEMS



32458LumiPlus RGB Pushbutton



27818Modulator with antenna LumiPlus RGB



32640Power Supply for RGB Micro (4 wires)



LumiPlus Control Motion Wireless

Control devices by modulator

RADIO FREQUENCY



41988 LumiPlus RGB Remote Control

EXISTING INSTALLATION



27818 LumiPlus RGB Modulator

WIFI



59131 LumiPlus WiFi Access Point

APP LumiPlus LED



59132 / 59133 (USA 115 Vac) LumiPlus WiFi Access Point Modulator







ODBUS



57434 LumiPlus Modbus



57435 LumiPlus Modbus Modulator

RGB DMX CONTROL SYSTEMS



41107 Modulator for RGB-DMX large projectors



41329 Astral DMX controller



52142Power Supply for RGB-DMX
Mini and Quadraled



41330 Astral DMX PRO controller



41106 Power Supply for RGB-DMX Micro projectors (4 wires)



51297Touch Screen DMX

